


Specifications


Nominal Voltage		12 V
Capacity (25°C)	20HR(10.5V)	24 Ah
	10HR(10.5V)	22.3Ah
	1HR(9.60V)	15Ah
Dimension	Length	166 ± 2mm (6.54inch)
	Width	175 ± 2mm (6.89inch)
	Height	125 ± 2mm (4.92inch)
	Total Height	125 ± 2mm (4.92inch)
Approx. Weight		7.8kg (17.2lbs) ± 4%
Terminal type		T3/T8
Internal resistance (Fully charged, 25°C)		Approx. 14m Ω
Capacity affected by temperature (20HR)	40°C	102%
	25°C	100%
	0°C	85%
	-15°C	65%
Self-discharge (25°C)	3 month	Remaining Capacity: 91%
	6 month	Remaining Capacity: 82%
	12 month	Remaining Capacity: 65%
Nominal operating temperature		25°C ± 3°C (77°F ± 5°F)
Operating temperature range	Discharge	-15°C ~ 50°C (5°F ~ 122°F)
	Charge	-10°C ~ 50°C (14°F ~ 122°F)
	Storage	-20°C ~ 50°C (-4°F ~ 122°F)
Float charging voltage(25°C)		13.60 to 13.80V Temperature compensation: -18mV/°C
Cyclic charging voltage(25°C)		14.50 to 14.90V Temperature compensation: -30mV/°C
Maximum charging current		7.2A
Terminal material		Copper
Maximum discharge current		360A(5 sec.)
Designed floating life(20°C)		10years



Dimensions



Terminal



- ◆ Absorbent glass mat technology;
- ◆ Recognized by UL & CE;
- ◆ ABS container.

Constant Current Discharge Characteristics (A, 25°C)


F.V/TIME	10min	15min	30min	60min	2h	3h	4h	5h	8h	10h	20h
9.60V	55.2	43.7	24.4	15.0	8.53	6.12	4.90	4.16	2.69	2.27	1.22
9.90V	53.5	42.7	23.9	14.7	8.48	6.08	4.87	4.14	2.68	2.26	1.21
10.2V	51.3	41.1	23.2	14.4	8.40	6.04	4.83	4.11	2.66	2.25	1.21
10.5V	49.1	39.7	22.6	14.1	8.27	6.00	4.80	4.08	2.64	2.23	1.20
10.8V	46.4	37.6	21.8	13.6	8.06	5.82	4.66	3.96	2.56	2.19	1.18

Constant Power Discharge Characteristics (Watt, 25°C)


F.V/TIME	10min	15min	30min	60min	2h	3h	4h	5h	8h	10h	20h
9.60V	623	498	279	173	99.8	72.7	58.3	49.7	32.3	27.2	14.6
9.90V	604	486	274	171	99.2	72.3	58.0	49.4	32.1	27.1	14.6
10.2V	579	468	265	166	98.3	71.8	57.6	49.1	31.9	26.9	14.5
10.5V	554	452	259	163	96.8	71.3	57.2	48.7	31.7	26.8	14.4
10.8V	523	428	249	158	94.3	69.1	55.5	47.3	30.7	26.2	14.1

Note: The above characteristics data can be obtained within three charge/discharge cycles.


Discharge Characteristics(25°C)




Charging Characteristics(25°C)




Effect of Temperature on Capacity




Self-discharge Characteristics




The Relationship for Open Circuit Voltage and Residual Capacity (25°C)



The Relationship for Charging Voltage and Temperature



Floating Life on Temperature



Cycle Life on D.O.D(25°C)

