


**Specifications**


Nominal Voltage		12 V
Capacity (25°C)	10HR(10.8V)	50Ah
	5HR(10.5V)	43.7Ah
	1HR(9.60V)	31Ah
Dimension	Length	258 ± 2mm (10.16inch)
	Width	133 ± 2mm (5.24inch)
	Height	200 ± 2mm (7.87inch)
	Total Height	200 ± 2mm (7.87inch)
Approx. Weight		16.5kg (36.4lbs) ± 4%
Terminal type		T9
Internal resistance (Fully charged, 25°C)		Approx. 7.5m Ω
Capacity affected by temperature (10HR)	40°C	102%
	25°C	100%
	0°C	85%
	-15°C	65%
Self-discharge (25°C)	3 month	Remaining Capacity: 91%
	6 month	Remaining Capacity: 82%
	12 month	Remaining Capacity: 65%
Nominal operating temperature		25°C ± 3°C (77°F ± 5°F)
Operating temperature range	Discharge	-15°C ~ 50°C (5°F ~ 122°F)
	Charge	-10°C ~ 50°C (14°F ~ 122°F)
	Storage	-20°C ~ 50°C (-4°F ~ 122°F)
Float charging voltage(25°C)		13.50 to 13.80V Temperature compensation: -18mV/°C
Cyclic charging voltage(25°C)		14.50 to 14.90V Temperature compensation: -30mV/°C
Maximum charging current		15A
Terminal material		Copper
Maximum discharge current		500A(5 sec.)
Designed floating life(20°C)		15years



**Dimensions**



**Terminal**



Terminal T9

- ◆ Absorbent glass mat technology;
- ◆ Recognized by UL & CE;
- ◆ ABS container.

**Constant Current Discharge Characteristics (A, 25°C)**


F.V/TIME	10min	15min	30min	60min	2h	3h	4h	5h	8h	10h	20h
9.60V	102	80.9	49.0	31.0	18.3	12.8	10.5	8.93	6.12	5.09	2.67
9.90V	98.8	78.9	48.0	30.5	18.2	12.7	10.4	8.87	6.08	5.08	2.67
10.2V	94.7	76.0	46.6	29.8	18.0	12.6	10.3	8.81	6.04	5.07	2.66
10.5V	90.6	73.4	45.4	29.2	17.7	12.5	10.3	8.75	6.00	5.04	2.64
10.8V	85.6	69.5	43.8	28.3	17.3	12.1	9.94	8.49	5.82	5.00	2.63

**Constant Power Discharge Characteristics (Watt, 25°C)**


F.V/TIME	10min	15min	30min	60min	2h	3h	4h	5h	8h	10h	20h
9.60V	1100	888	550	353	212	150	123	105	72.7	60.8	32.1
9.90V	1067	866	539	348	210	149	122	105	72.3	60.7	32.0
10.2V	1023	834	522	339	208	148	121	104	71.8	60.5	31.9
10.5V	979	806	510	333	205	147	121	103	71.3	60.1	31.7
10.8V	924	763	491	322	200	143	117	100	69.1	59.7	31.5

Note: The above characteristics data can be obtained within three charge/discharge cycles.


**Discharge Characteristics(25°C)**




**Charging Characteristics(25°C)**




**Effect of Temperature on Capacity**




**Self-discharge Characteristics**




**The Relationship for Open Circuit Voltage and Residual Capacity (25°C)**



**The Relationship for Charging Voltage and Temperature**



**Floating Life on Temperature**



**Cycle Life on D.O.D.(25°C)**

